




LP Series-General Purpose

LP12-45(12V45Ah)




Specifications

Rated Voltage	12V	
Nominal Capacity	45.0Ah	(C ₁₀ , 1.80V/cell)
Dimension	Length	197±2mm (7.76 inches)
	Width	165±2mm (6.50 inches)
	Container Height	170±2mm (6.69 inches)
	Total Height	170±2mm (6.69 inches)
Approx Weight	14.2 Kg (31.3 lbs)	
Terminal	M6	
Container Material	ABS	
Rated Capacity (25°C)	47.8 Ah	(20hr, 2.39A, 1.80V/cell)
	45.0 Ah	(10hr, 4.50A, 1.80V/cell)
	39.4 Ah	(5hr, 7.88A, 1.75V/cell)
	35.7 Ah	(3hr, 11.9A, 1.75V/cell)
	30.2 Ah	(1hr, 30.2A, 1.60V/cell)
Max. Discharge Current	450A (5s)	
Internal Resistance (25°C)	Approx 9.0mΩ	
Operating Temp. Range	Discharge	-15 ~ 50°C (5 ~ 122°F)
	Charge	-20 ~ 40°C (-4 ~ 104°F)
	Storage	-15 ~ 40°C (5 ~ 104°F)
Nominal Operating Temp. Range	25±3°C (77±5°F)	
Cycle Use	Initial Charging Current less than 13.5A. Voltage	
	14.4V~15.0V at 25°C(77°F)Temp. Coefficient -30mV/°C	
Standby Use	Initial Charging Current less than 13.5A. Voltage	
	13.5V~13.8V at 25°C(77°F)Temp. Coefficient -20mV/°C	
Effect of temp. to Capacity	40°C (104°F)	103%
	25°C (77°F)	100%
	0°C (32°F)	86%
Self Discharge	LP series batteries may be stored for up to 6 months at 25°C(77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.	



Layout



Constant Current Discharge (Amperes) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	93.7	69.9	58.2	48.9	37.6	28.1	23.7	17.8	14.2	10.7	8.55	7.15	6.21	5.04	4.22	2.26
1.80V/cell	109.2	82.4	67.7	56.4	42.5	31.4	26.2	19.5	15.5	11.6	9.22	7.70	6.66	5.40	4.50	2.39
1.75V/cell	119.1	88.4	71.6	59.2	44.4	32.7	27.2	20.1	16.0	11.9	9.45	7.88	6.80	5.50	4.57	2.42
1.70V/cell	129.0	94.3	75.7	62.3	46.4	33.9	28.2	20.8	16.5	12.3	9.69	8.05	6.94	5.60	4.64	2.45
1.67V/cell	134.7	97.7	78.1	64.0	47.6	34.7	28.8	21.2	16.7	12.5	9.82	8.15	7.02	5.65	4.68	2.46
1.60V/cell	148.5	105.8	83.7	68.2	50.3	36.5	30.2	22.1	17.4	12.9	10.1	8.40	7.22	5.79	4.78	2.51


Constant Power Discharge (Watts/cell) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	178.0	133.8	111.9	94.3	72.7	54.4	46.1	34.7	27.8	21.0	16.8	14.1	12.2	10.0	8.34	4.49
1.80V/cell	204.3	155.9	128.7	107.6	81.5	60.4	50.7	37.7	30.1	22.7	18.1	15.1	13.1	10.6	8.89	4.74
1.75V/cell	219.5	165.2	134.8	111.8	84.5	62.4	52.2	38.8	30.9	23.2	18.4	15.4	13.3	10.8	9.02	4.79
1.70V/cell	233.9	173.8	140.8	116.5	87.4	64.2	53.7	39.8	31.7	23.8	18.8	15.7	13.6	11.0	9.14	4.85
1.67V/cell	241.9	178.8	145.6	119.0	89.1	65.4	54.6	40.4	32.1	24.0	19.0	15.9	13.7	11.1	9.21	4.88
1.60V/cell	259.9	189.5	151.9	124.8	92.9	68.0	56.7	41.8	33.2	24.8	19.6	16.3	14.0	11.3	9.38	4.97



LP Series-General Purpose

LP12-45(12V45Ah)



Applications

- All purpose
- Uninterruptable Power Supply (UPS)
- Electric Power System (EPS)
- Emergency backup power supply
- Alarm and security system
- Communication power supply
- DC power supply
- Auto control system


General Features

- 10 years design life(25°C)
- Special exhaust structure and sealing technology, safe and reliable, flexible installation, convenient maintenance
- PbCaSn alloy for plate grids: less gassing, less self-discharging
- High quality AGM separator: extend cycle life and prevent micro short circuit
- High purity raw material: ensure low self discharge rate


Standards

- Compliance with IEC 60896 standards, EU Battery Directive
- UL, CE Certified
- Manufactured in Leoch® IATF 16949, ISO 45001, ISO 9001 and ISO 14001 certified production facilities


Discharge Characteristics




Float Charging Characteristics



Temperature Effects in Relation to Battery Capacity



Effect of Temperature on Long Term Float Life



Sales Offices Worldwide

China Sales Office

5th Floor, Xinhua Bldg., Nanhai Blvd.,
Nanshan, Shenzhen, China. 518052
Tel: +86-755-86036060 (100 lines)
Fax: +86-755-26067269
E-mail: export@leoch.com

North America Sales Office

19751 Descartes
Foothill Ranch, CA 92610, USA
Tel: 949-588-5853
Fax: 949-588-5966
E-mail: sales@leoch.us
Http://www.leoch.us

HongKong Sales Office

Workshop C, 33/F, TML Tower, No. 3 Hoi Shing Road,
Tsuen Wan, New Territories, Hong Kong
Tel: +852 35786666
Fax: +44 1452 729428 / 1452 729696
E-mail: sales.hk@leoch.com

UK Sales Office

9B Wheatstone Court, Waterwells, Business Park,
Gloucester, GL2-2AQ, UK United Kingdom
Tel: +44(0) 1452 729428 / 1452 729696
Fax: +44 1452 690125
E-mail: Sales.Europe@leoch.com
Http://www.leoch.eu

Singapore Sales Office

No. 1 Tech Park Crescent,
Singapore 638131
Tel: +65 68636078
Fax: +65 6863 6079
Email: sales.sg@leoch.com

EMEA Sales Office

1 Deligiorgi St., 121 31 Athens,
Greece
Tel: +30 210 5760318 (2 lines)
E-mail: support_EMEA@leoch.com
Http://www.leoch.eu

Australia Sales Office

2/29 Tarlington Place, Smithfield, NSW 2164
Australia
Tel: 02 9756 0950
E-mail: sales.au@leoch.com

India Sales Office

Shed no. A-53(b), 2nd Stage of Peenya Industrial Area,
Bangalore North Taluk, Bangalore-560058, India
Tel: +91-80-23440018/23440019
Fax: +91-80-23440017
E-mail: indiasales@leoch.com



[Http://www.leoch.com](http://www.leoch.com)

© 2020 LEOCH. All rights reserved.

Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.
Subject to revisions without prior notice.

Publication No.: LB-LP12-45-PD-EN-V2.1-202110